

Beta Arc 130

Arc Stick MMA Welding
Power Source

Applications

- Maintenance
- Light Industrial
- Sheet Metal Industry
- Service Engineers
- Fencing & Security
- Hobbies & Home Users

Processes

- Stick (MMA) Welding
- Scratch TIG
(optional Tig Kit Required)

Input Power: 240v 1ph. 50/60Hz

Output Power Range: 10—130amps D.C.

Weight: 3.5 Kg

Dimensions: 260 x 130 x 175 mm

Beta Arc 130

Uses the latest Inverter technology to produce a small portable, extremely lightweight welding machine with an excellent duty cycle.

Ideal for many applications where portability and space/weight requirements are restricted.

This 35% duty cycle machine is capable of MMA (Stick) welding utilising electrodes from 1.6mm to 3.2mm in most metals from mild steel through stainless steels, nickel alloys, cast irons, bronzes etc.

The smooth D.C. output gives a stable arc characteristic resulting in high integrity, low spatter welds requiring minimum post weld clean up.

The infinitely variable output allows the user to accurately match the requirement of various electrodes, joint configurations and material thicknesses

Built in thermal overload protection



- High Quality
- Inverter Technology
- Industrial Duty cycle
- Portable
- Lightweight
- Infinitely variable
- Thermal overload protection
- Sturdy sheet metal case
- Single Phase input
- CE marked & certified

Beta Century

“A new name in welding machines backed by 70 years of experience to give you better value and reliability “

Beta Century

Beta Century (UK) Ltd.
Leading Suppliers of High Technology
Welding & Plasma Cutting Machines

Beta Century (UK) Ltd. 59, Main Street, Thornley, Leeds, LS14 3BU.
Tel: +44 (0) 113 2893118 Fax: +44 (0) 113 2893118 Mobile: +44 (0) 7917 300020
Email: sale@betacentury.co.uk
Registered office: 3, Bull Lane, St.Ives, Cambs PE27 5AX. Company Reg. N° 5383454

Specifications (Subject to alteration without notice)

Technical Information

Input power voltage (V)	AC 230V +- 10% 1ph.
Frequency (Hz)	50/60
Input Rating (KVA)	4.14
Open Circuit Voltage (OCV)	50
Output Current range (A)	10—130
Rated Output Voltage	25.2
Duty Cycle (%)	130 Amps @ 35%
No-Load power (W)	20
Efficiency (%)	85
Power factor (COS ϕ)	0.93
Insulation Class	IP23
Weight (kg)	3.5
Overall dimensions (mm)	260 x 130 x 175
Diameter of electrodes	1.6mm, 2.0mm, 2.5mm, 3.2mm

Warranty

This equipment is warranted against failure occurring due to faulty workmanship or materials and comes with a 2 year return to base warranty from date of purchase.

Package includes: -

- **Power Source**
- **Primary Cable**
- **Welding Leads with Electrode holder, earth clamp and European standard connecting plugs**
- **Welding shield**
- **Wire Brush/Chipping hammer**
- **Rugged Plastic carrying case**
- **Carrying Shoulder strap**

Optional Extras: P.O.A.

Scratch Start TIG welding Kit Comprising - 4metre Valved Tig Torch with cable, Argon Regulator Accessory kit.