

Beta Arc 250

Arc Stick MMA Welding
Power Source

Applications <ul style="list-style-type: none">• Fabrication Industry• Maintenance• Process Pipework• Fencing & Security• Agricultural Engineering• Pipeline Construction	Processes <ul style="list-style-type: none">• Stick (MMA) Welding• Scratch TIG (optional Tig Kit Required)	Input Power: 380v 3ph. 50/60Hz Output Power Range: 20—250amps D.C. Weight: 19 Kg Dimensions: 480 x 205 x 355 mm
---	--	--

Beta Arc 250

Uses the latest Inverter technology to produce a robust professional lightweight welding machine with an industrial duty cycle.

Ideal for workshop and construction site use, a portable yet rugged 3 phase input machine for demanding applications where a high duty cycle is required.

This 60% duty cycle machine is capable of MMA (Stick) welding utilising electrodes from 1.6mm to 5.0mm in most metals from mild steel through stainless steels, nickel alloys, cast irons, bronzes etc. including Cellulosic (E6010) type electrodes.

The smooth D.C. output gives a stable arc characteristic resulting in high integrity, low spatter welds requiring minimum post weld clean up.

The infinitely variable output and digital display allows the user to accurately match the requirement of various electrodes, joint configurations and material thicknesses

Built in thermal overload protection



- High Quality
- Inverter Technology
- Industrial Duty cycle
- Portable
- Lightweight
- Infinitely variable
- Thermal overload protection
- Three Phase input
- Rugged Metal Construction
- CE marked & certified

Beta Century

“A new name in welding machines backed by 70 years of experience to give you better value and reliability “

Beta Century

Beta Century (UK) Ltd.
Leading Suppliers of High Technology
Welding & Plasma Cutting Machines

Beta Century (UK) Ltd. 59, Main Street, Thornor, Leeds, LS14 3BU.
Tel: +44 (0) 113 2893118 Fax: +44 (0) 113 2893118 Mobile: +44 (0) 7917 300020
Email: myers.thorner@btopenworld.com
Registered office: 3, Bull Lane, St.Ives, Cambs PE27 5AX. Company Reg. N° 5383454

Specifications (Subject to alteration without notice)

Technical Information

Input power voltage (V)	AC 380V +- 15% 3ph.
Frequency (Hz)	50/60
Input Rating (KVA)	9.4
Open Circuit Voltage (OCV)	54
Output Current range (A)	20—250
Rated Output Voltage	30
Duty Cycle (%)	250 Amps @ 60%
No-Load power (W)	60
Efficiency (%)	85
Power factor (COS ϕ)	0.93
Insulation Class	B
Protection Class	IP21
Weight (kg)	19
Overall dimensions (mm)	480 x 205 x 355
Diameter of electrodes	1.6mm, 2.0mm, 2.5mm, 3.2mm,4.0mm,5.0mm

Warranty

This equipment is warranted against failure occurring due to faulty workmanship or materials and comes with a 2 year return to base warranty from date of purchase.

Package includes: -

- **Power Source**
- **Primary Cable**
- **European standard connecting plugs**

Optional Extras: P.O.A.

Scratch Start TIG welding Kit Comprising - 4metre Valved Tig Torch with cable, Argon Regulator Accessory kit.