

Beta Cut 160

Three phase Air Plasma Cutting System

Applications <ul style="list-style-type: none">• Fabrication Industry• Process Pipe work• Construction Industry• Pipeline construction• Commercial Vehicle Repairs• Demolition/Scrap metal processing	Processes <ul style="list-style-type: none">• Air Plasma Cutting	Input Power: 380v 3ph. 50/60Hz Cutting Capacity: 48mm Output Power : 20—160 amps Weight: 53Kg Dimensions: 670 x 333 x 590 mm
---	---	---

Beta Cut 160

Uses the latest Inverter technology to produce a Plasma Cutting machine with an industrial duty cycle. 160 amps @80% duty cycle

Ideal for the heavy Structural industry for plasma cutting and gouging

This rugged unit is capable of cutting 48mm in most metals

The infinitely variable output and digital display allows the user to accurately set the power to match the material thicknesses

Can be powered by a generator for on site situations where there is no mains power available

Comes complete with a cutting torch & cable. Air filter/regulator included in the package

Built in thermal overload protection



- 48mm Capacity
- High Quality
- Inverter Technology
- Industrial Duty cycle
- Portable
- Lightweight
- Infinitely variable
- Thermal overload protection
- Rugged Metal Construction
- Three Phase input
- CE marked & certified

Beta Century

“A new name in welding & Plasma Cutting machines backed by 70 years of experience to give you better value and reliability “

Beta Century

Beta Century (UK) Ltd.
Leading Suppliers of High Technology
Welding & Plasma Cutting Machines

Beta Century (UK) Ltd. 59, Main Street, Thornor, Leeds, LS14 3BU.
Tel: +44 (0) 113 2893118 Fax: +44 (0) 113 2893118 Mobile: +44 (0) 7917 300020
Email: myers.thorner@btopenworld.com
Registered office: 3, Bull Lane, St.Ives, Cambs PE27 5AX. Company Reg. N° 5383454

Specifications (Subject to alteration without notice)

Technical Information

Input power voltage (V)	AC 380V +- 15% 3ph.
Frequency (Hz)	50/60
Input Rating (KVA)	30
Open Circuit Voltage (OCV)	275
Output Current range (A)	20-160 amps
Rated Output Voltage	144
Duty Cycle (%)	100 Amps @ 80%
Arc-Starting	Un-touch
Efficiency (%)	85
Power factor (COS ϕ)	0.93
Insulation Class	B
Protection Class	IP21
Weight (kg)	53
Overall dimensions (mm)	670 x 333 x 590
Max. Cutting Thickness (mm)	48
Required Air Pressure (Bar)	5.0—6.0
Compressed Air Volume	0.5 m ³ /min (17.7 CuFt/min)
Air Quality	Dry Compressed Air

Warranty

This equipment is warranted against failure occurring due to faulty workmanship or materials and comes with a 2 year return to base warranty from date of purchase.

Package includes: -

- **Power Source**
- **Primary Cable**
- **Cutting Torch/Cable**
- **Earth return/Work Cable with clamp**
- **Air Regulator/Filter unit**
- **Starter Spares pack**

Beta Century

*Beta Century (UK) Ltd.
Leading Suppliers of High Technology
Welding & Plasma Cutting Machines*

Beta Century (UK) Ltd. 59, Main Street, Thornor, Leeds, LS14 3BU.
Tel: +44 (0) 113 2893118 Fax: +44 (0) 113 2893118 Mobile: +44 (0) 7917 300020
Email: myers.thorner@btopenworld.com
Registered office: 3, Bull Lane, St.Ives, Cambs PE27 5AX. Company Reg. N^o: 5383454